

2 in 1 Mosaic Tile Adhesive & Grout

COMPANY INFORMATION

ALLGEMEINE BAU - CHEMIE PHIL., INC.

Address: 10/F Asian Star Building, 2404 Asean Drive, Filinvest City, Alabang, Muntinlupa City 1781 Philippines

Tel: (+63 2) 88426891 ■Fax: (+63 2) 88427146 ■info@abc.ph ■www.abc.ph

PRODUCT NAME

ABC 2 in 1 Mosaic Tile Adhesive & Grout

PRODUCT DESCRIPTION

ABC 2 in 1 MOSAIC TILE ADHESIVE & GROUT is specially formulated for faster and more convenient Mosaic Tile Installations. It bonds and grouts ceramic, porcelain, stoneware & glass mosaic tiles all in one step

THE 2 in 1 TILE ADHESIVE & GROUT ADVANTAGE

- High Adhesive Strength
- Non-sag
- Non-fading & Uniform Color
- Eco-friendly & Low VOC Levels
- Time Saving
- Waterproof
- Professional Finish
- **Durable & Crack Free**



White, Gray, Bahama Beige, Mint Green, Black, Dark Brown, Sorento Blue, Dark Blue

CLASSIFICATION STANDARD

- PNS ISO 13007 1:2014 Philippine National Standards Int'l Organization for Standardization
- PNS ISO 13007 3:2014 Philippine National Standards Int'l Organization for Standardization
- ANSI A118.6 American National Standards Institute

TECHNICAL DATA

Properties	Results
Open Time	15 - 20 mins.
Grouting Time	40 mins.
Pot Life	1 hour
Standing Strength	Superior
Slip Resistance	0 mm* *based on 4 inches granite tile
Tensile Adhesion Strength (28 days)	2 Mpa = 290 psi
Tensile Adhesion Strength after water immersion (21 days)	0.50 Mpa = 72.50 psi
Compressive Strength (28 days)	16 Mpa = 2,320 psi

COVERAGE

 $2kg \frac{ABC 2in1}{Mosaic Tile deliberate 3 Count} = 0.46 \text{ m}^2$

Note: Calculation based on 5 pieces of 30 x 30cm mosaic tile sheets using a 6 x 6mm notched trowel.

SURFACE PREPARATION

The surface must be fully cured, structurally stable, level, even, clean and free from paint & contaminants such as dirt, dust, loose material, oils and chemicals. The use of a level bar is essential to ensure levelness and / or plumbness of the surface. For painted surfaces, acid etch or abrade paint to ensure proper bonding.

APPLICATION GUIDE

The ABC 2 in 1 System

Step 1 Caution: Use only non-absorptive materials as mixing base (plastic pail or galvanized iron sheets). If absorbent materials such as plywood, wooden box, gypsum board, fiber cement board or card-board is used, it will affect the chemical properties of the product, which can result in bonding failure & poor product performance.

Pour clean water and add ABC 2 Mixing Ratio in 1 powder. Stir to attain a lumpfree, creamy consistency. Use immediately after mixing.

Step 2 ■ Dampen surface before applying ABC 2 in 1.

- Spread ABC 2 in 1 with the use of 6mm x 6mm notched trowel and position mosaic tiles immediately or within the OPEN TIME of 20
- Press on the mosaic tiles with the use of a rubber float to

ensure good contact and coverage. Use tile spacers to ensure proper alignment and carefully remove before adhesive sets. Let the tiles set for around 40 minutes and check for tile movement by applying pressure to ensure a good bond.

TIP: Use tile spacers for uniform grout lines & perfect alignment.

Step 3 ■ Start grouting only when tile adhesive has reached its initial setting time of 40 minutes. With the use of a rubber squeegee, spread the grout diagonally across the tiles, filling tile joints uniformly.


Step 4 ■ Wait for 5 minutes and Curing Time remove excess mortar using a damp sponge in diagonal strokes.

hours ■ Remove haze using a clean, damp and lint-free cloth. Don't allow excess mortar to harden on tile since it will be difficult to clean.











Grouting





APPLICATION AREAS

Exterior areas such as swimming pool, fountain and others



CLEANING & SAFETY

Do not let material cure and harden on tools, mixing pail and equipment. Clean immediately with water after use. Avoid eye exposure and prolonged skin contact. Do now swallow or ingest. In case of irritation, rinse with sufficient water.

PACKAGING

2 kg plastic bag

STORAGE & SHELF LIFE

When stored in a cool dry place & in its original unopened packaging, ABC 2 in 1 Mosaic Tile Adhesive & Grout will remain usable one year from date of manufacture.

Due to variety of applications, different working methods and the various properties of bases, we cannot assume responsibility or liability with regard to the application of our products. Our guarantee and liability are restricted to the quality of our products at the time of acceptance of the customer of such products. In no case shall our liability extend beyond replacement of defective products, if any, found at the time of acceptance. For all deliveries and services, our General Sales Condition including warranties stipulated for each case are valid.