


Tile Adhesive QUICK-GUIDE







🧦 Baumax Pro Tips



For tile adhesive application thickness greater than 6mm (e.g. large format tiles & medium to thick bed), use the double spreading method (on the substrate and the back of the tile).
 If the back of a tile is too smooth, apply a Scratch Coat to roughen the surface for easier wall installations.

3 Always comb mortar in straight manner lines to allow air release ensuring 100% mortar coverage.

COVERAGE of 25kg Tile Adhesive					
Tile Size	Adhesive Thickness (minimum)	Coverage (approx.)			
mosaic and smaller than 30 x 30cm	3mm	5m²			
60 x 60cm & smaller	6mm	2.6m ²			
larger than 60 x 60cm	10mm	1.6m ²			

NOTE: Coverage is dependent on tile size, surface smoothness of the back of the tile, substrate condition and adhesive application thickness. The bigger the tile, the smaller the coverage area.

	Redifix Slurry		Coverage* (approx)		
	4L REDIFIX + 25kg ORIGINAL	8 - 9m²			
	Redifix Modified Tile Adhesive		3mm	5m²	
		Adhesive thickness	6mm	2.6m ²	
46			10mm	1.6m ²	

*Note: Adhesive coverage is dependent on tile size, surface smoothness of the back of the tile, substrate condition and application thickness. The bigger the tile, the smaller the coverage area.



TILING 101 Mobile App

TILING 101

TILING PRODUCTS

- granolithic

flooring

- glass

Know all the ABC products you can use to perfect your tile installations!

TILE GROUT COLOR VIEWER

Take a photo of your tile & select among the wide range of grout colors which best match your tile installation!

PRODUCT CONSUMPTION CALCULATOR

Get quick results to estimate your product





