

MULTIBOND Vinyl, Carpet & Wood Adhesive

COMPANY INFORMATION

ALLGEMEINE BAU - CHEMIE PHIL., INC.
 Address: 10/F Asian Star Building, 2404 Asean Drive,
 Filinvest City, Alabang, Muntinlupa City 1781 Philippines
 Tel: (+63 2) 88426891 ■ Fax: (+63 2) 88427146 ■ info@abc.ph ■ www.abc.ph

PRODUCT NAME

MULTIBOND Vinyl, Carpet & Wood Adhesive

PRODUCT DESCRIPTION

MULTIBOND is a high strength ready-to-use water-based vinyl, carpet & wood adhesive, suitable for installations of various decorative floor and wall finishes. Its advanced polymer technology ensures high bonding strength - twice the bonding strength of contact cement. Its thick formulation with body allows it to correct minor surface imperfections and fill gaps between the substrate for an even and professional finish.



MULTIBOND is an ABC eco-friendly product which has low Volatile Organic Compound (VOC) levels bearing little or no adverse effects to the environment. Majority of its components are natural and contain no harmful chemical additives & odors, creating a safe living environment for you and your family.

THE ABC MULTIBOND ADVANTAGE

- Fast & Easy
- Water Resistant
- Odorless & Non-toxic
- Nail free installation
- No shrinkage
- High bonding strength
- Water based



CLASSIFICATION STANDARD

- ✓ PNS ISO 17178:2014 (PH) Philippine National Standards International Organization for Standardization
- ✓ PNS 1994 : 2004 (PH) Philippine National Standards

TECHNICAL DATA

Dry curing	Parquet	Tensile strength (PNS ISO 17178 : 2014)	1.30 Mpa (Passing: 1 MPa)
	Vinyl	Shear strength (PNS 1994 : 2004)	0.55 Mpa (Passing: 0.29 MPa)
Bonding results for wet curing		Good	
Base		Water based	
Trowelability		Easy to spread	
Toxicity		Non-toxic	
Application		On substrate only	

SURFACE PREPARATION

The surface must be fully cured, structurally stable and level. Make sure the surface is clean and free from paint & contaminants such as dirt, dust, loose material, oils and chemicals. If needed, acid etch the surface area to be applied (e.g. on existing polished or waxed floors).

APPLICATION GUIDE

1. Application

Spread MULTIBOND over a clean and dry surface and comb evenly with a recommended notched trowel.

Note: Using a notched trowel will prevent lump formation, as it enhances the adhesive's body to correct minor surface imperfections.



Finishing	Notched Trowel Size
vinyl tiles, linoleum, rubber backed	1.5 x 1.5 mm
wood parquet, wood planks, carpet tiles & other rough finish	

2. Installation


Wait 15 minutes, then positioning each piece of vinyl tile or parquet before tamping with a rubber float.

COVERAGE


$$4\text{kg MULTIBOND} = 20 - 24\text{m}^2$$

Note: Calculation based using a 1.5mm x 1.5mm notched trowel. Actual consumption is dependent on substrate condition.

SECTIONAL DETAIL



DECORATIVE FINISHES



PACKAGING

4kg plastic container

STORAGE & SHELF LIFE

When stored in a cool dry place & in its original unopened packaging, Multibond Vinyl, Carpet & Wood Adhesive will remain usable one year from date of manufacture.

WARRANTY

Due to variety of applications, different working methods and the various properties of bases, we cannot assume responsibility or liability with regard to the application of our products. Our guarantee and liability are restricted to the quality of our products at the time of acceptance of the customer of such products. In no case shall our liability extend beyond replacement of defective products, if any, found at the time of acceptance. For all deliveries and services, our General Sales Condition including warranties stipulated for each case are valid.